




ATLANTIC PORT MORIEN



The latest-trending colours in Clay Brick

In response to industry demand for a contemporary and sophisticated brick, we introduced the Atlantic Port Morien a few years ago. Atlantic Port Morien has a black coal appearance with a modern feel - a look that can easily be applied to both residential and commercial applications.

New light grey and white bricks added this year

New for this year, we are introducing two more neutral colour variations to the Atlantic Collection: a light grey we've named Cape Smokey; and a white brick, fittingly called White Point.

The Atlantic Collection from Shaw Brick is the embodiment of the latest clay brick colour trends, which are black bricks, all shades of grey, white and even deep reds. These clean, cool shades top the trends of all home price ranges - primarily whites with white mortar and all grays from light steel to charcoal.

Same brick texture as our Tapestry Collection

The Atlantic Collection features the same lightly-textured finish of the <u>Tapestry Collection</u> that lends a refined character and allows the colours to show their best.

Drop into a <u>Shaw Retail Centre</u> or one of our <u>independent dealers</u> to see samples of these bricks for sale and to learn more about any product in the Shaw Masonry Collection.



20 Clay Brick Way Lantz, NS B2S 3G4 (902) 883-2201 salesinfo@shawbrick.ca shawbrick.ca

SPECIFICATIONS

Brick Measurement Chart

Sizes	Metric	Imperial	Approximate Weight	Pc/Pallet	Coverage
Modular	57x90x190mm	2 1/4" x 3 1/2" x 7 5/8"	4lbs	500	7 pcs/sqft
Saxon	90x90x190mm	3 ½" x 3 ½" x 7 5/8"	6lbs	305	4.9 pcs/sqft
Max 57	57x90x255mm	2 ¼" x 3 ½" x 10 1/8"	5lbs	400	5.2 pcs/sqft
Ontario	60x102x213mm	2 3/8" x 4" x 8 3/8"	5lbs	395	6 pcs/sqft
CSR	70x90x230	2 3/4" x 3 1/2" x 9 1/16"	6lbs	380	4.9 pcs/sqft
MAX	79x90x290	3 1/8" x 3 1/2"x 10 1/8"	7lbs	276	3.9 pcs/ sqft
Slender	12.7x90x190mm	1/2" x 3 1/2" x 7 5/8"	28lbs/box	34pcs/box	7 pcs/ sqft

Note: Not all bricks are available in all sizes as indicated. Please contact your Shaw Brick Sales Representative or email salesinfo@shawbrick.ca for minimum special order quantities and production lead times.

Clay Brick Product Specifications

CSA STANDARD VS. SHAW – TYPICAL TEST REPORT								
Property	CSA	SHAW BRICK						
, , , , , , , , , , , , , , , , , , ,	Standard A82-06	Red	Brown	Buff				
Minimum Compressive Strength Gross Area MPa (P.S.I.)	20.68 (3,000)	80 – 100 (11,000 – 14,000)	70 – 90 (10,000 – 13,000)	65-85 (9,500 – 12,000)				
Maximum Water Absorption 24 hr. %	8.0	1 – 3	2 – 4	6 – 8				
Maximum Saturation Coefficient	0.78	0.65 – 0.78	0.50 – 0.70	0.70 – 0.78				
Maximum Initial Rate of Absorption	30g/min/ 20,000mm ²	1 – 5	5 – 20	10 – 20				
Freeze Thaw % After 50 Cycles	Less than 0.5% loss in dry mass		Meets Requiremer	nts				

To view more photos and for more information on this product, visit: shawbrick.ca/products/atlantic-port-morian/