

20 Clay Brick Way Lantz, NS B2S 3G4 (902) 883-2201 salesinfo@shawbrick.ca shawbrick.ca

Olde English











20 Clay Brick Way Lantz, NS B2S 3G4 (902) 883-2201 salesinfo@shawbrick.ca shawbrick.ca

Clay brick with century-old warmth and character.

The Olde English Collection from Shaw Brick combines the timeless charm of century-old brickwork with the exceptional strength and durability of modern craftsmanship. Each brick is uniquely textured and shaded, featuring subtle colour variations and a distressed surface that adds authentic character to any project. This collection is perfect for creating distinctive, enduring designs with a touch of historical elegance.

COLOUR





Essex

Winchester

SHAPE





Max 57

Metric Modular

TEXTURE



Rustic

ADDITIONAL INFORMATION/SPECIFICATIONS

BRICK MEASUREMENT CHART

Sizes	Metric	Imperial	Approximate Weight	Pieces per Pallet	Coverage
Modular	57 x 90 x 190 mm	2 1/4" x 3 1/2" x 7 5/8"	4 lbs	500	7 pieces/sq. ft.
Max 57	57 x 90 x 255 mm	2 1/4" x 3 1/2" x 10 1/8"	5 lbs	400	5.2 pieces/sq. ft.



20 Clay Brick Way Lantz, NS B2S 3G4 (902) 883-2201 salesinfo@shawbrick.ca shawbrick.ca

Minimum Compressive Strength - Gross Area MPa (P.S.I.)

Red: 80-100 (11,000-14,000) Brown: 70-90 (10,000-13,000) Buff: 65-85 (9,500-12,000)

Maximum Water Absorption (24 hr. %)

Red: 1 - 3 Brown: 2 - 4 Buff: 6 - 8

Maximum Saturation Coefficient

Red: 0.65 - 0.78 Brown: 0.50 - 0.70 Buff: 0.70 - 0.78

Maximum Initial Rate of Absorption

Red: 1g/min/5,000mm2 Brow: 5g/min/20,000mm2 Buff: 10g/min/20,000mm2

Freeze Thaw % After 50 Cycles - Meets Requirements